

Order No.:

CJUA8-18M-NA
CJUA8-18M-NB
CJUA8-18M-PA
CJUA8-18M-PB
CJUA8-18M-DA
CJUA8-18M-DB
CJUA8-18M-ADA
CJUA8-18M-ADB

Features

- Special optical design on the product's back cover, providing 360° visible indicator lights.
- Dedicated IC, stable ultra-long detection distance, and strong anti-interference capabilities.
- Uses durable, oil-resistant cables.
- Detection surface made of oil-resistant, corrosion-resistant material, offering strong environmental resistance.

Wiring



Accessory

Serrated Flange Nuts *2

Overall dimension



Technical Parameters

General description	
Switch point function	NPN 、PNP、D 、AD
Rated operating distance Sn	8mm
Installation	Non-Flush mounting
Standard detector	36*36*1t(Q253A)
Reliable operating distance Sa	0...6.4mm
Rated grade	
Rated voltage UB	DC10...30V(Including fluctuation (p-p) 10%
Switching frequency f	0.4KHz
Hysteresis range	≤ 15% of sensing distance
Repeatability	<3% of detection distance
No load current Io	<12mA
Voltage drop Ud	NPN/PNP:<3V； DC two-wire<6V
Working current IL	＜200mA
Leakage current	＜100uA
Circuit protection	Reverse polarity protection, short-circuit protection
Switching state indication	Red LED indicator
Surrounding environment	
Ambient temperature	-25℃...70℃ (No icing,no condensation)
Temperature effect	-Within 25 ℃... 70 ℃, within 15% of detection distance at+24 ℃
Ambient humidity	35...95%RH (No condensation)
Influence of voltage	<3%
Mechanical properties	
Wiring	2m standard cable
Shell material	Brass plated with pearl nickel
Sensing surface	PBT
Protection level	IP67
Withstand Voltage	AC 500V , 50/60Hz 1 minute between the whole charging part and the shell
Insulation resistance	≥20 MΩ (DC 500 V with a megohmmeter) between the whole charging part and the shell
Vibration resistance	10～55 Hz, complex amplitude 1.5mm, 2H in X, Y and Z directions
Certification and Standards	
Product certification	CE CCC CQC ISO9001 ISO14001 ISO45001
Unit weight	About 110g

The datasheet is subject to change without notice. Copyright Cheemi Tech